

60X60X25 mm

JF0625-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Amp)	Noise (dBA)	Weight (g)
JF0625B1TRAL	B	12	10.2 ~ 13.8	36.24	0.578	7200	0.38	4.56	0.38	49.5	59
JF0625B1TR	B			29.69	0.422	6000	0.37	4.44	0.38	42.5	
JF0625B1UR	B,H			26.96	0.357	5500	0.29	3.48	0.30	39.6	
JF0625-1S	B,H, S			24.27	0.292	5000	0.22	2.64	0.22	37.2	
JF0625-1H	B,H, S			21.44	0.237	4500	0.20	2.40	0.23	34.1	
JF0625-1M	B,H, S			19.00	0.185	4000	0.16	1.92	0.20	31.3	
JF0625-1L	B,H, S			16.76	0.145	3500	0.13	1.56	0.17	27.3	
JF0625-1E	B,H, S			14.24	0.108	3000	0.11	1.32	0.11	22.4	
JF0625-1V	B,H, S			11.72	0.076	2500	0.08	0.96	0.08	20.2	
JF0625B2TRAJ	B	24	20.4 ~ 27.6	35.15	0.552	7000	0.21	5.04	0.21	48.3	
JF0625B2TR	B			29.69	0.422	6000	0.20	4.80	0.21	42.5	
JF0625B2UR	B,H			26.96	0.357	5500	0.16	3.84	0.16	39.6	
JF0625-2S	B,H			24.27	0.292	5000	0.13	3.12	0.14	37.2	
JF0625-2H	B,H, S			21.44	0.237	4500	0.12	2.88	0.17	34.1	
JF0625-2M	B,H, S			19.00	0.185	4000	0.11	2.64	0.13	31.3	
JF0625-2L	B,H, S			16.76	0.145	3500	0.10	2.40	0.12	27.3	
JF0625-2E	B,H, S			14.24	0.108	3000	0.07	1.68	0.07	22.4	
JF0625-2V	B,H, S			11.72	0.076	2500	0.06	1.44	0.06	20.2	
JF0625B4UR	B,H	48	40.8 ~ 55.2	26.96	0.357	5500	0.11	5.28	0.11	39.6	
JF0625B4SR	B,H			24.27	0.292	5000	0.09	4.32	0.09	37.2	
JF0625B4HR	B,H, S			21.44	0.237	4500	0.07	3.36	0.08	34.1	
JF0625B4MR	B,H, S			19.00	0.185	4000	0.06	2.88	0.07	31.3	
JF0625B4LR	B,H, S			16.76	0.145	3500	0.05	2.40	0.06	27.3	

Specifications subject to change without notice

The 7th character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM".

Please contact us for detail if your request bearing system is not shown in the above list.

